



DP2200/SL SLIMLINE DualPROX® PROXIMITY READER

PRODUCT DESCRIPTION

The DualPROX® reader designed by JTI Technologies reads both old PAC and new 125kHz type cards and tokens. It provides two simultaneous data outputs, one for connection to PAC controllers, and the other a selectable 26-bit or 44-bit Wiegand data output.

The Wiegand data output format can be connected to most access control systems. The PAC serial output can be connected directly to PAC 1000, PAC 1100, PAC 2000 and PAC 2100 controllers. It will simulate a PAC reader and can be connected to the controller's reader port without an interface. Token and card codes are the same as from a PAC reader.

The DualPROX® allows installers and system integrators to easily integrate with many different types of host system controllers for which they only need to stock one type of reader regardless of the system they intend to use it with.

End users can use the DualPROX® reader on existing PAC systems and it also provides the option of migrating to other manufacturers' access control systems without the need to change readers or tokens.



SPECIFICATIONS

Electrical

Supply Voltage:	9Vdc to 24Vdc
Current Requirement:	< 110 mA

Physical

Dimensions (mm):	116 x 40 x 17 (H x W x D)
Colour:	Black (White and Grey available on request)
Material:	ABS Plastic - Stabilised against Ultra Violet Light
Rating:	IP66 - suitable for outdoor and indoor use

Environmental

Operating Temperature:	-30°C to 50°C Ambient
------------------------	-----------------------

Data Output

Wiegand:	26-bit or 44-bit Wiegand (selectable) for use with a wide range of tokens/cards and controllers
PAC:	PAC compatible serial data for use with old and new PAC tokens/cards and controllers Other data outputs available on request.

Connection

Pigtail Cable Length:	0.5m
Cable Gauge:	7/0.2, 0.22mm stranded
Conductors:	8 core screened

Operational

Reading Range:	Up to 80mm depending upon the type of token or card
Buzzer Operation:	Controlled by host controller (active low)
LED Operation:	One red 4mm LED and one green 4mm LED. Red LED normally on -blinks when token or card is read. Green LED lights when signal received from host controller on the LED line (active low)

DP2200/SL SLIMLINE DualPROX® PROXIMITY READER

Connection Details

RED	+V
Black	0V
White	Data 1
Green	Data 0
Blue	PAC Data Signal
Yellow	LED
Orange	Select Wiegand 26-bit (to 0v) or 44-bit (to +V)
Brown	Buzzer

Alternative Products

DP2200/V	Vandal resistant <i>DualPROX®</i> reader
DP2200/P	Panel mounted <i>DualPROX®</i> reader

Ordering Information

DP2200/SL	Slimline <i>DualPROX®</i> reader
DP-Card-n	<i>DualPROX®</i> card with standard Nortech logo
DP-Card-c	<i>DualPROX®</i> card with custom logo
DP-Card-b	<i>DualPROX®</i> card blank
DP-Fob-n	<i>DualPROX®</i> Key fob standard Nortech logo
DP-Fob-c	<i>DualPROX®</i> Key fob with custom logo

Please contact BC Technology Sales or Sales Support departments for placing orders or further information

Tel: 01933 405050 Fax: 01933 405454 Email: sales@bctechnologyltd.co.uk